

26OPzS-ET 4550 SOLAR

Vented Flooded Deep Cycle Battery



Performance characteristics

Nominal Voltage	2V
Number of cells	1
Design Life	20 years

Nominal Capacity 25°C (77°F)

120 hour rate (39A, 1.85V)	4687Ah
48 hour rate (90A, 1.80V)	4320Ah
10 hour rate (368.2A, 1.8V)	3682Ah

Internal Resistance

Fully Charged Battery 25°C (77°F)	0.11mOhm
-----------------------------------	----------

Electrolyte

Nominal S.G at 25°C = 1.240kg/l

Operating Temperature Range

-20~55°C

Maximum Discharge Current 25°C (77°F)

3446A

Charge Methods: Constant Voltage Charge 25°C (77°F)

Cycle use	2.40V (time limited)
Maximum charging current	1472A
Standby use	2.25V ± 1%
Temperature compensation	-3.0mV/°C/Cell

Terminal Torque

23Nm

Features

High energy density

Robust tubular positive electrode design, compliant with DIN 40736

Minimal maintenance due to low antimony alloy and large electrolyte volume

Operating temperature -20°C to +55°C

Low self discharge rate of approximately 3% per month at 20°C

EUROBAT design life: Long Life >12 years

Fully recyclable with low CO₂ footprint

High cyclic performance

3000+ cycles @ 60% DOD @ IUI charging

Applications

Solar/Wind Power Stations

Traffic Systems

Hydro Power Generation

Off Grid Solutions

Telecommunications/ Mobile Phone Stations


Power Distribution Companies

Capacities C10-C240

Cell Type Ue (100%) / VPC	C10	C12	C20	C24	C48	C72	C100	C120	C240
Ref Temp	25°C	25°C	25°C	25°C	25°C	25°C	25°C	25°C	25°C

26OPzS-ET 4550 SOLAR	3682	3723	4046	4147	4320	4530	4268	4687	4874
----------------------	------	------	------	------	------	------	------	------	------

Cycles vs DOD of OPzS Solar Power



ET/DATAOPZSSOLAR 4550V2 0521

Compliant with IEC 60896-11 / IEC 61427

Dimensions and weight

Length	212 mm
Width	575 mm
Height (H1)	772 mm
Total height (H2)	785 mm
Dry weight	159.5 kg
Filled weight	222.0 kg

